

NPK 13-15-35

TECHNICAL SPECIFICATION

1. TYPICAL ANALYSIS :

| CHARATERISTICS : | UNIT : | TYPICAL : | GUARANTEED |
|-------------------------------|--------------------|-------------|------------|
| Purity of NPK | w/w % | 99.0 | 99.0 |
| K | w/w % | 28.8 | min 28.0 |
| K ₂ O | w/w % | 34.7 | min 33.8 |
| N | w/w % | 13.2 | min 13.0 |
| P | w/w % | 6.55 | max 7.2 |
| P ₂ O ₅ | w/w % | 15.0 | max 16.5 |
| Na | w/w % | 0.05 | max 0.15 |
| Ca | w/w % | 0.05 | max 0.2 |
| Cl | w/w % | 0.05 | max 0.2 |
| Perchlorate | ppm | <0.1 | |
| Hypochlorite | ppm | ND | |
| Nitrite | ppm | ND | |
| Heavy metals | ppm | < 10 | < 10 |
| Cd | ppm | < 2 | max 2 |
| Pb | ppm | < 5 | max 5 |
| Hg | ppm | <0.1 | max 0.1 |
| Water insolubles | w/w % | 0.01 | max 0.05 |
| Anticaking agent | w/w % | 0.1-0.15 | max 0.15 |
| Bulk density loose | t / m ³ | 1.00 - 1.19 | max 1.2 |
| pH | | 4.0-6.0 | max 7 |

| SIEVE ANALYSIS | µm | CUMULATIVE w / w % |
|----------------|-----|-----------------------|
| | 650 | 10 |
| | 350 | 50 |
| | 170 | 90 |
| | 130 | 95 |
| | 80 | 99 |

NPK 13-15-35

TECHNICAL SPECIFICATION

2. ANALYTICAL METHODS :

| CHARACTERISTICS : | METHODS : |
|-------------------|--|
| K | ASTM 2011 vol 11.01 D4192-08 |
| N | Standard method for the Examination water & waste water 21st edition (4 – 120) |
| Cl | AASTM 2011, vol 11.01, D512-10 |
| Na | AOAC 2005, 18th Edition, method 974.01 ch 2 page 39 (2.6.26) |
| Ca | AOAC 2005, 18th Edition, Method 965.09 ch 2, p 29 |
| P | AOAC 2005, 18th Edition, Method 958.01, Chapter 2, p.6 |
| Heavy metals | ASTM 2011 vol 11.01 D3557-02-D, D3559-08-D |
| Humidity | AOAC 2005, 18th Edition, Method 950.01, Chapter 2, p.4 |
| Water insolubles | AOAC 2005, 18th Edition, Method 925.55 - C |
| Anticaking agent | UV spectrophotometry determination 284 nm |

NPK 13-15-35

4 . PACKING / STORAGE :

1200 Kg, 1000 Kg, or 25 kg bags.
1000 kg net shrink-wrapped pallet.

NPK 13-15-35 is a hygroscopic product sensitive to moisture and big temperature variations.
In order to avoid any risk of caking or product deterioration, NPK 13-15-35 must only be stored in a dry, ventilated and covered area.

5. USES :

Direct application, NPK and NK granulation or ammoniation, NPK and NK bulk blending, liquid and suspension fertilizers, fertigation (sprinkler, mini sprinklers and drip irrigation), foliar sprays, foliar NPK fertilizers, starter and transplant solutions, winter hardener, winter breaking dormancy sprays, flowering inducement sprays.

6 . CROPS :

Flowers, vegetables, strawberries, potted plants, soilless culture,
(in door and out door), tobacco, potatoes, fruit trees, grapes, citrus,
pineapples, cotton, bananas, mango, olives, home gardens, lawns.

7 . PRODUCTION SITE :

Arab Fertilizers & Chemicals Industries Ltd.
(KEMAPCO®)
P.O.BOX 2564 Aqaba 77110 Jordan
TEL.: +96232017174
FAX: +96232017181
E-mail : kemapco@kemapco.com.jo

**COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY SGS
=ISO 9001=**



جائزة
المصدر
الأردني



First Cycle (2014/2015)
First place

Jordanian
Exporter
Award